

MG07SCA SERIES

ENTERPRISE CAPACITY HDD

The MG07SCA Enterprise Capacity HDD series provide capacities up to 14 TB^[1] and 7,200 rpm performance, in a robust design engineered for nearline business-critical workloads.

The MG07SCA series utilize industry-standard 3.5-inch^[2] 26.1 mm height form factor and Advanced Format sector technologies for optimum capacity and data reliability. Toshiba Persistent Write Cache technology helps enhance performance while also maintaining data integrity in the event of a sudden loss of power. Equipped with 12 Gbit/s^[4] SAS interface, the Enterprise Capacity MG07SCA series help save rack space and reduce the footprint and operational burden of business critical servers and storage systems.

512e or 4Kn Advanced Format sector technology models are available. 4Kn models (MG07SCAxxxA/AY) offer optimum performance and compatibility with 4K-capable applications and operating environments. 512e models (MG07SCAxxxE/EY) are broadly supported today and also help provide support for legacy applications and operating environments that require 512 B sector lengths.



Product image may represent a design model.

KEY FEATURES

- Industry Standard 3.5-inch 26.1 mm Height Form Factor
- Large Capacity (14 TB and 12 TB Models)
- 7,200 rpm Performance
- Dual-Port 12 Gbit/s SAS Interface
- MTTF of 2,500,00M hours
- 550 total TB Transferred per Year Workload Rating^[5]
- Rotational Vibration (RV) Sensors
- 4Kn or 512e Advanced Format Sector Technology
- Toshiba Persistent Write Cache Technology to help Maintain Data Integrity during Power-Loss Events

APPLICATIONS

- Engineered for Mid-line / Nearline Business Critical Workloads
- Tier 2 Business-Critical Servers and Storage Systems
- Servers Supporting Application Workloads that Benefit from High Capacity per Spindle
- Capacity-Optimized Data Center Storage Systems
- Object and File Storage Solutions
- Enterprise Data Protection and Tiered Storage Infrastructure

SPECIFICATIONS

Item		MG07SCA14T	MG07SCA12T
Interface		SAS-3	
Formatted Capacity ^[1]		14 TB	12 TB
Performance	Interface Speed ^[6]	12.0 Gbit/s, 6.0 Gbit/s, 3.0 Gbit/s, 1.5 Gbit/s	
	Rotation Speed	7,200 rpm	
	Buffer Size	256 MiB ^[7]	
	Maximum Sustained Data Transfer Speed ^[6] (Typ.)	248 MiB/s	242 MiB/s
Logical Data Block Length	MG07SCAxxxA/AY (fixed length)	4,096 B / 4,160 B / 4,224 B	
	MG07SCAxxxE/EY (emulation) ^[8]	Host:512 B, Disk:4,096 B Host:520 B, Disk:4,160 B Host:528 B, Disk:4,224 B	
Supply Voltage	Allowable Voltage	12 V ^[9] ± 10 % / 5 V ^[9] + 10% / -7% ^[10]	
Power Consumption	Random Write / Read 4KB Q1 (Typ.)	8.28 W	7.80 W
	Active Idle (Idle-A)	4.73 W	4.36 W
Acoustics ^[11]	Active Idle (Typ.)	20 dB	

ENVIRONMENTAL LIMITS

Item		Specification
Ambient temperature	Operating	5 °C to 55 °C
	Non-Operating ^[12] ^[13]	-40 °C to 70 °C
Relative Humidity	Operating	5 % to 90 % R.H. (No condensation)
	Non-Operating	5 % to 95 % R.H. (No condensation)
Altitude	Operating	- 305 m to 3,048 m
	Non-Operating ^[12] ^[13]	- 305 m to 12,192 m
Shock ^[14]	Operating	686 m/s ² { 70 G } (2 ms duration)
	Non-Operating	2,450 m/s ² { 250 G } (2 ms duration)
Vibration ^[14]	Operating ^[15]	7.35 m/s ² { 0.75 G } (5 to 300 Hz) 2.45 m/s ² { 0.25 G } (300 to 500 Hz)
	Non-Operating ^[16]	29.4 m/s ² { 3.0 G } (5 to 500 Hz)

RELIABILITY

Item	Specification
MTTF ^[17]	2,500,000 hours
Non-recoverable Error Rate	10 error per 10 ¹⁶ bits read
Load / Unload	600,000 times
Availability	24 hours/day, 7 days/week
Rated Annual Workload (Total TB Transferred per Year, R/W)	550 TB per year

MECHANICAL SPECIFICATIONS

Item	Specification
Width (Max)	101.85 mm
Height (Max)	26.1 mm
Length (Max)	147.0 mm
Weight (Max.(Typ.))	720 g (694 g)

[1] Definition of capacity: Toshiba defines a terabyte (TB) as 1,000,000,000,000 bytes. A computer operating system, however, reports storage capacity using powers of 2 for the definition of 1TB = 2⁴⁰ = 1,099,511,627,776 bytes and therefore shows less storage capacity. Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system, such as Microsoft Operating System and/or pre-installed software applications, or media content. Actual formatted capacity may vary.

[2] "3.5-inch" mean the form factor of HDDs. They do not indicate drive's physical size.

[4] Read and write speed may vary depending on the host device, read and write conditions, and file size.

[5] Workload is defined as the amount of data written, read or verified by commands from host system.

[6] The maximum sustained data rate and interface speed may be restricted to the response speed of host system and by transmission characteristics.
1 Gbit/s = 1,000,000,000 bits/s. 1 MiB/s = 1,048,576 bytes/s

[7] A mebibyte (MiB) means 2²⁰, or 1,048,576 bytes.

[8] Read-modify-write is supported.

[9] Input voltages are specified at the HDD connector side, during HDD ready state.

[10] Make sure the value is not less than -0.3V DC (less than -0.6V, 0.1ms) when turning on or off the power.

[11] The measuring method is based on ISO 7779.

[12] Non-operating condition(except storage condition) assumes short term transportation.

[13] The range of altitude is 3,048 m or less. Up to 55°C at 7,620m. Up to 40°C at 12,192m.

[14] Vibration applied to the HDD is measured at near the mounting screw hole on the frame as much as possible.

[15] At random seek write/read and default on retry setting with log sweep vibration.

[16] At power-off state after installation

[17] MTTF (Mean Time to Failure) is not a guarantee or estimate of product life; it is a statistical value related to mean failure rates for a large number of products which may not accurately reflect actual operation. Actual operating life of the product may be different from the MTTF.

• Before creating and producing designs and using, customers must also refer to and comply with the latest versions of all relevant TOSHIBA information and the instructions for the application that Product will be used with or for.

• Company names, product names, and service names may be trademarks of their respective companies.